PLYMIJVENT®

clean air at work

STACK ADAPTER

TAILPIPE ADAPTER

The FBC stack adapter is compatible with Plymovent's VSR railsystem to extract exhaust emissions from fire and emergency service stations as well as military facilities.

The adapter mounts directly to the vehicle's exhaust pipe so that it can enter the VSR catcher and easily glide into the rubber seal of the VSR profile.



APPLICATIONS

The Stack Adapter is intended to be used for the following applications:


 To eliminate hazardous vehicle exhaust emissions with our vehicle exhaust capture and removal systems for the following segments: fire and emergency service stations as well as military facilities.

SPECIFICATIONS

■ Physical dimensions and properties				
Material	zinc-plated steel			
■ Ambient conditions				
Max. relative humidity	all ambient conditions allowed			
Storage conditions	all ambient conditions allowed			
■ Where used				
As adapter to regular vertical tailpipes enabling the vehicle to enter the VSR system.				
■ Scope of supply				
FBC stack adapter				
■ Order information				
Article no.	see remaining specifications			
Number/package	1			
■ Shipping data				
Gross weight	3 kg			
Packing dimensions	500 x 500 x 300 mm			
Harmonized Tariff Code	84219990			
■ Mounting				

The stack adapter should be adjusted accordingly to allow the top edge of the adapter to protrude 40 - 50 mm above the bottom edge of the aluminum rail profile. If needed, an extension can be added to the tailpipe to reach the required height.

REMAINING SPECIFICATIONS



		Dimensions (mm)		
Article	Art. no.	A	В	С
FBC-83	0000114620	158	370	83
FBC-93	0000114621	188	370	93
FBC-113	0000114619	225	370	113
FBC-118	0000114622	260	370	118
FBC-135	0000114623	310	370	135
FBC-4	0000114624	225	370	100
FBC-5	0000114625	303	370	125
FBC-6	0000114626	413	370	150

Product type FBC stack adapter
Article no. see remaining specifications

Product category tailpipe adapters
Version 210319/0

Always check the latest version on www.plymovent.com